



The GSM Mobile Communicator provides a reliable and cost effective solution for notification of fault and alarm conditions on Identileak and Identi-Cryer control panels.

With the 'R Control' mobile app notification and reporting is simple allowing multiple users access to the same communicator and users allowed access to multiple communicators, helping early notification in the event of an incident. Alerts can also be customised allowing flexibility to the building owners.

The communicator comes with 2 years subscription as standard making it a easy out of the box solution.



Specification

Supply Voltage	12-29 Vdc
Number of Inputs	2 Inputs (Programmable)
Number of Outputs	2 Outputs (Programmable)
Current Consumption	50mA (Standby), 200ma (Peak)
Colour	PCB only
Dimensions (HxWxD)	63x90x32 mm
Weight	73g

Part Numbers

IC3/GSM	GSM Mobile Communicator + 2 Years Subscription
IC3/GSM/2	GSM 2 Year Subscription
IC3/GSM/R	GSM Reactivation Code

IDENTI**CRYER**
IDENTILEAK

Features

- / Allows instant notification of fault or alarm.
- / Multiple users allowed for same devices.
- / Users can have access to multiple devices.
- / Ideal for notification of Water Leaks or Lockdowns.
- / Wiring looms supplied for panel wiring.

 **MADE IN THE UK BY VIMPEX**

3700169_REV0100

We reserve the right to change or amend any design or specification in line with our policy of continuing development and improvement.

VimpeX Ltd, Star Lane, Great Wakering, Essex, SS3 0PJ, UK
 VimpeX Europe BV / VimpeX Sweden AB /

+44 (0) 1702 216 999 / sales@vimpeX.co.uk / vimpeX.co.uk

Registered in England No.2915112 Registered Address: Star Lane, Great Wakering, Essex, SS30PJ, United Kingdom

