

9-30750

Spare Stratos Micra 25 detector

Description

Detector only, supplied without docking station.

The Stratos Micra 25 is designed to provide very high sensitivity smoke detection in a small package.

ClassiFire Perceptive Artificial Intelligence ensures that the detector operates at optimum sensitivity for the protected environment, without the need for complex setup. This means the product will configure itself to provide high sensitivity in a computer room or reduced sensitivity in a smoky area.

The detector is designed to fit into a Docking Station. All sampling pipes and cables are connected to the Docking Station as a first fix operation leaving the detector to be fitted during the final commissioning phase if required. This ensures that detectors are less likely to be damaged during the installation.

Upgradable volt-free Fire and Fault relay outputs are available for remote monitoring by local fire detection or BMS systems.

Typical Applications

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

Options Available

- Addressable Protocol Interface Cards APIC™ available
- Command Module available for central monitoring and display
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.



Details

- Ultra small low cost aspirating smoke detector for easy and discreet installation
- High sensitivity provided by laser based forward light scattering technology for early warning
- Single sampling pipe up to 50m in length (still air)
- Unique ClassiFire® Perceptive Artificial Intelligence dynamically adjusts the detector's operating parameters to day changes in the protected environment and dust contamination
- Unwanted alarms from dust are avoided using patented Laser Dust Discrimination Technology LDD 3D3 Laser Dust Discrimination and
- RS485 communications built in as standard for networked communications
- CPR, LPCB, VdS, NF & CSIRO approved

9-30750

Spare Stratos Micra 25 detector

Technical specifications

General

Status indication	LED
Alarm levels	4 (Aux, Pre-alarm, Alarm and Alarm 2)

Electrical

Operating voltage	21.6 to 26.4 VDC
Current consumption	250 mA

Detection

Detection principle	Laser light scattering mass detection and particle evaluation
Range	0.0015 to 25% (%Obs/m)
Particle sensitivity range	0.003 μ to 10 μ

Sampling pipe

Length	50 m maximum run (25 m in moving air)
Inlet quantity	1
Inlet size	27 mm OD
Exhaust	1 (optional)

Input

Input quantity	Expansion: Optional input and relay card
----------------	--

Output

Output quantity	2 - Alarm (n/o) and Fault (n/c) Expansion: Optional input and relay card
Output type and rating	500 mA @ 30 V

Physical

Physical dimensions	145 x 220 x 85 mm (W x H x D)
Net weight	1.7 kg
Colour	Cream
Mounting type	Wall mount
Cable entries	2 x M20
Material (body)	Sheet steel enclosure

Environmental

Operating temperature	-10 to +60°C (EN54-20)
Relative humidity	0 to 90% noncondensing
Environment	Indoor
IP rating	IP40

Regulatory

Certification	EN54-20
---------------	---------

Sampling pipework

Sampling holes	up to 10
----------------	----------

Networking

SenseNET (RS-485)	On-board
-------------------	----------



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 28 July 2025 - 11:50