

200m2 Meeting/Seminar Room Hearing Loop Kit

Part No. AKM1



Overview

- Includes a PDA200E hearing loop amplifier, APM omni-directional plated microphone and 6m of Belden cable.
- Ideal for creating a high quality hearing loop system for a meeting or seminar room.
- Wall-mountable PDA200E amplifier capable of driving a perimeter loop of up to 200m2.
- Internal drive, level and metal compensation controls.
- Two balanced / unbalanced line level inputs, one 100V line input and one microphone input with 12V phantom power for electret microphones.
- Full compatibility with the Outreach plate audio input extension system.
- Fully compliant with BS EN 60118-4 when correctly installed.
- APM microphone provides up to 25m2 ambient coverage or 2.5m2 direct speech coverage from a ceiling height of 2.5 to 3m.
- Loop cable not included our LOOP2W 1mm2 cable is suitable for most applications. If in doubt contact our technical department for advice.



More Information

Technical Specifications

Wall mounting. Requires fixed Mains wiring. Type

Coverage 200m2 approx. Mains supply

Auxiliary inputs $1\ x$ Microphone, $2\ x$ Line/Outreach and $1\ x$ 100V line inputs via screw connectors.

Indicators Input level; loop current meter (peak 3, 2, 1); compression; power on.



T 01942 322744



















Controls Input level; loop drive, metal compensation. Product dimensions (mm) W 228 x H 155mm x D 42mm (amplifier only). Construction & finish White painted steel (PDA200E); plastic (AKM1).

IP Rating IP20 (PDA200E & AKM1). Weight 1 kg (amplifier only).

Operating conditions/temperature -5 $^{\circ}$ C to +40 $^{\circ}$ C. Max relative humidity: 95%.

 $PDA200E\ 200m2\ induction\ loop\ amplifier;\ APM\ omni-directional\ plated\ microphone;\ 9m\ Belden\ cable;\ Loop\ applied\ property and\ pr$ Kit contents

Fitted sticker. Loop cable IS NOT included.



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom















