

ActiV Conventional Hi-Output Wall Voice Sounder (deep base)

Part No. **BF446C/CC/DR**

**C-TEC
Manufactured**



Overview

- Superb sound intelligibility.
- Choose from two evacuation voice messages and four evacuation alarm tones (your selected evacuation message will be preceded by the selected tone).
- Alarm Current at 30Vdc = 10mA.
- Alarm Current at 18Vdc = 8mA.
- IP33C rated.
- Manufactured in the UK by C-TEC.



Technical Specifications

Protocol/compatibility	Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use)
Application/operation	Designed to be wall mounted. Can be used in covered outdoor areas.
VAD category & coverage	N/A.
Flash rate & colour	N/A.
Supply/operating voltage	18 to 30V DC.
Nominal SPL (Sound Pressure Level)	88dB(A) @ 1m.
Alarm current	At 30Vdc: 10mA; At 18Vdc: 8mA.
Product dimensions (mm)	114mm diameter x 132mm deep.
IP Rating	IP33C (Type B).
Weight	315g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).

