

ActiV High 75°C Fixed Temp. Heat Detector

Part No. C4403B



Overview

- A high-quality Type B high fixed temperature (75°C) heat detector offering outstanding detection performance at a very competitive
- Manufactured by C-TEC in the UK.
- Third-party certified to EN54-5 by Intertek.
- Wide 6-33V DC operating voltage.
- Two 8mm x 2mm ultra-bright red LED indicating strips offering 360° visibility.
- Compatible with our ActiV C4408D diode, C4408 non-diode and C4408R relay bases.





More Information

Technical Specifications

Approvals/certifications Certified to EN54-5 by Intertek.

Application/operation Generates an alarm condition when it detects a temperature of between 69°C & 85°C .

Application temperature 40°C typical, 65°C max. Static response temperature 69°C typical, 85°C max.

2-wire monitored, polarity sensitive. Supply wiring

Supply/operating voltage 9 to 33V DC. Quiescent current 30μA @ 24 VDC. Alarm voltage 6-33V DC.



T 01942 322744

















F 01942 829867

E sales@c-tec.co.uk

W www.c-tec.com











19mA @ 12-33V DC; 11mA @ 9V DC; 2.5mA@ 6V DC. Alarm current Alarm reset voltage Less than 1V DC (+0.5 seconds alarm reset time)

Remote LED output available via ActiV base. Current source to the negative line, short-circuit protected. Max Expansion connections

voltage 2.7V DC

102.2mm diameter x 37mm deep (detector in base); 102.2mm diameter x 57.5mm deep. Product dimensions (mm)

Construction & finish White polycarbonate casing rated to UL94 V-2 with nylon parts.

IP Rating IP42. Weight 99g.



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom















