

Stainless Steel Emergency Assistance Alarm Kit

Part No. **NC951/SS**



Overview

- A high-quality brushed stainless steel single zone emergency assistance alarm.
- Attractively designed, easy to install and simple to use.
- Allows a distressed person to raise an alarm in the event of an emergency. To operate, the user pulls the cord of the ceiling pull to activate a light and sounder outside the WC and on the system's Call Controller.
- Includes an NC941/SS 12V Stainless Steel Call Controller, NC806CS/SS Stainless Steel Overdoor Light c/w Sounder, NC809DB/SS Stainless Steel Reset Point and an NC807C Plastic Ceiling Pull.
- Can be wired in 4 core stranded security cable.
- Suitable for use in some high-profile disabled persons toilet alarm applications. Please note, if a fully BS8300 compliant accessible toilet alarm system is required consider using our NC951 standard plastic kit instead.



Technical Specifications

Mains supply	230V 50/60Hz (36mA max. current). 50Hz frequency.
Internal power supply	13-13.8V d.c.
Total output current limited to	250mA.
Quiescent current	See individual device listings for NC941/SS, NC807C, NC806CS/SS and NC809DB/SS
Max battery size and type	A remote battery back-up kit (part no. NC941B) can be connected to the NC941/SS to ensure it remains operational for a limited amount of time in the event of Mains failure.
Alarm current	TBC.
Auxiliary relays	N/A.
Indicators	NC807C & NC809DB/SS have red Reassurance LEDs; NC806CS/SS has twin red Alarm LEDs. NC941/SS has a red Alarm and green Supply Present LED;
Controls	NC941/SS has a Reset button which can be optionally disabled; NC807C has a pull cord with two bangles to generate a call; NC809DB/SS has a Reset button.
Expansion connections	For applications requiring more than one point of call (e.g. at the WC and the wash basin), up to 3 ceiling pulls can be daisy chained together.
Call acknowledgement functionality	No. If this feature is required consider using our NC951 Accessible Toilet Alarm instead.
Onboard Sounder	Yes (on NC806CS and NC941/SS).
Onboard Infrared Receiver	No.
Product dimensions (mm)	156 W x 94 H x 37 D (NC941/SS); 87 W x 87 H x 80 D (NC806CS/SS); 87 W x 87 H x 24 D (NC809DB/SS). Ceiling pull measures 93mm diameter x 27 D.
Packaging dimensions (mm)	285 W x 201 H x 55 D mm (size of NC951/SS kit box containing all items).
Construction & finish	Brushed stainless steel call controller, reset point and overdoor light; Plastic ceiling pull.
IP Rating	IP41 (all wall mounting devices); IP21 (ceiling pull).
Weight	995kg.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.
Notes	For multi-zone stainless steel call systems consider using one or more of our NC944/SS call controllers and an NC930/SS 12V power supply.