



### Product Number: 64 Wood filler

#### DESCRIPTION:

This product is a water-based general purpose wood filler. It can withstand temperatures up to 1000°C

#### PHYSICAL DATA:

Type:	Water-based
Colour:	Natural
Viscosity:	Paste
Specific Gravity:	1.00 – 1.10

#### RECOMMENDATION FOR USE:

Application methods:	Putty Knife or paint scraper
Conditions during application:	Temperature of air & substrate must be above 5°C
Drying time:	Variable depending on thickness and ambient conditions

#### DIRECTIONS FOR USE:

STIR WELL before use

It is advisable to wear gloves, although the wood filler is non-toxic, safe handling practices should still be implemented to avoid irritating sensitive skin.

If glue makes contact with eyes, flush thoroughly with water for at least 15 minutes.

Seek medical attention. For skin wash with soap and water.

The surface must be clean, free from all loose materials, dust, dirt, oil, and any other contaminants.

Apply with a putty knife or paint scraper by pasting over the hole or crack.

For deep holes apply Wood filler in several layers, allowing each layer to dry between applications.

Larger applications may shrink and crack on drying. Re-apply wood filler.

Clean tools with water.

#### MISCELLANEOUS:

Size of containers: 250ml, 500ml and 1 litre

Remarks: Frost-free freight and storage.

Shelf Life: 12 months in unopened original packaging (Stored between 5-30°C)