

WEATHERGUARD SITE TRIPOD

IP65 NON-CORROSIVE FITTINGS C/W TRIPOD HEADS & TRIPOD

Quick and easy to deploy, Weatherguard Site tripod mounted fittings offer ultimate flexibility on site. The heads are supplied ready to mount onto the tripod, complete with 2x110V power outlets and 5m of cable.



Features

- Height adjustable tripod
- Fast and easy to set up on site
- For use with Weatherguard Site tripod heads
- Yellow finish



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS/TP	Weatherguard Site Adjustable Tripod				

Product Information

IP Rating	IP65
IK Rating	IK07
Material (Body/Housing)	Steel

Colour Rendition (CRI)	Ra >80
Approval	UKCA CE



WEATHERGUARD SITE TRIPOD

IP65 NON-CORROSIVE FITTINGS C/W TRIPOD HEADS & TRIPOD

Packaging Information

Dimensions (mm)	L: 1280 x W: 1050 mm
Product Net Weight (kg)	3.7 kg
Barcode	5055807622783

Box Dimensions (mm)	L: 1340 x W: 180 x D: 175 mm
Box Gross Weight (kg)	4.25 kg

